

Item Specification Sheet

Media Environment Design

P.O. Box 1863
Carlsbad, CA 92018 United States of America
(760) 434-9040

INTEGRA DPC-8.5

6-DISC MULTI FORMAT CAROUSEL DVD/CD CHANGER



Dimensions

Height:	5.16
Width:	17.13
Depth:	17.17

Located In

#

Main House: Living Room

1

Multi-Format Capability

In addition to offering playback of high-resolution SACD and DVD-Audio discs, this changer reads MP3, CD-R/RW and DVD-R/RW. Integrated bass management tailors the audio signals to best match your speaker configuration. Audio discs may even be played back randomly for hours of uninterrupted music.

Outstanding Audio Quality

Performance is not sacrificed for the convenience of holding six discs. With high-resolution digital-to-analog converters, which incorporate our exclusive Vector Linear Shaping Circuitry, you are guaranteed the superb audio quality your home theater deserves. For maximum flexibility, programmable Dual Direct Digital Paths are used to carry this signal straight from the disc to the on the rear panel.


Superior Video

The DPC-8.5 has the power to produce stunning video images with increased dimensionality, getting the most out of your DVD collection. It features Direct Progressive Scan, which includes 2-3 pull-down processing for smoother video from film-based sources, a high-speed Video DAC, and video outputs that are all active simultaneously.

Convenience

An intuitive icon-based, on-screen display makes setup and operation very user-friendly. Load in six of your favorite music discs for true Random Play of conventional CDs, SACDs, and MP3 encoded discs. Harnessing all of this technology are a preprogrammed, multi-brand remote control and unmatched system integration features.

Qty: 1 **INTEGRA DPC-8.5**



Item Specification Sheet

Media Environment Design

P.O. Box 1863
Carlsbad, CA 92018 United States of America
(760) 434-9040

INTEGRA DTA-9.4

7 CHANNEL HOME THEATER AMPLIFIER



Dimensions

Height: 6.88

Width: 17.13

Depth: 17.81

Located In

#

Main House: Living Room

1

The DTA-9.4 is designed specifically for multichannel home theater, with adequate power to effortlessly handle the large transients that today's DVD soundtracks require. The high output current switching power supply features 156,000 microfarads of capacitance for nearly inexhaustible current reserves, and complete compatibility with low impedance 4 ohm speaker loads. Built around a newly designed seven-channel high current amplifier, the DTA-9.4 is capable of delivering 120 Watts per channel into 8 ohm, and 240 Watts per channel into 4 ohm!

At the heart of the DTA-9.4 is our new VL Digital Pulse Width Modulation (PWM) technology. This can be thought of as digital remastering for your entire home theater - delivering smooth, accurate sonic reproduction. For more on this new technology, [click here for the DTA-9.4 Whitepaper](#).

Each channel of the DTA-9.4 features a completely independent circuit topology for superior sonic reproduction and fidelity. The amplifier benefits from an ultra low internal impedance design, thanks to the extensive use of copper bus bars and heavy-gauge wiring, which provide superior response to transients and variations in the speaker load.

For use with compatible equipment, such as the Integra DTC-9.4 preamplifier/processor/tuner, the amplifier features gold plated balanced XLR inputs for improved signal transfer. There are also high quality gold-plated terminals for standard unbalanced connections to A/V controllers. Newly developed heavy-duty gold plated speaker terminals accept thick spade plugs, heavy gauge speaker wire, and banana plugs.

The DTA-9.4 - one button says it all... Power!

Qty: 1 **INTEGRA DTA-9.4**



Item Specification Sheet

Media Environment Design

P.O. Box 1863
Carlsbad, CA 92018 United States of America
(760) 434-9040

SONANCE CINEMA SELECT LCR

8 CINEMA THX LEFT, CENTER, RIGHT SPEAKER



Dimensions

Height:	20.25
Width:	11.56
Depth:	3.87

Located In

#

Main House: Living Room


3

Sonance Cinema® Select in-wall speakers bring true cinema performance to those with smaller theater rooms. In fact, earning THX select certification guarantees that in rooms up to 2,000 cubic feet, Cinema Select speakers will reproduce film soundtracks just as their filmmakers intended them to sound. By incorporating the latest materials and technologies, Cinema Select speakers perform just as impressively with music as they do with film soundtracks, while their paintable aluminum grilles and small footprint let them practically disappear into the décor.

Specifications

- Tweeter 1" (25mm) silk dome, ferrofluid-cooled, shielded magnet
- Woofer 6 1/2" (165mm) carbon fiber cone, rubber surround, shielded magnet
- Frequency Response 80Hz - 20kHz ±3dB
- Impedance 8 ohms nominal; 5 ohms minimum
- Power Handling 5 watts minimum; 135 watts maximum
- Sensitivity 90dB (2.83V/1 meter)
- Grille Material - Perforated aluminum
- Cutout Dimensions WxH 6 13/16" x 10 11/16" (172mm x 270mm)
- Shipping Weight 5lbs (2.3kg) each

Qty: 3 **SONANCE CINEMA SELECT LCR**



Item Specification Sheet

Media Environment Design

P.O. Box 1863
Carlsbad, CA 92018 United States of America
(760) 434-9040

SONANCE S623TR

6.5 IN-CEILING SPEAKER



Dimensions

Height:	9.75
Width:	9.75
Depth:	5.19

Located In	#
Main House: Master Bedroom	2
Main House: Bedroom 1	2
Main House: Kitchen	2

With a 6-1/2" carbon fiber woofer and 1" silk dome tweeter, the S623TR is at home playing movie soundtracks or Mozart sonatas. The woofer assembly and the tweeter pivot to direct sound at listeners, and the tweeters acoustic back chamber smoothes and extends its performance. A 3-position tweeter adjustment switch lets you fine-tune the speaker's response to the installation. The RotoLockÆ mounting system makes installation quick and easy.

Specifications:

- Tweeter: 1" (25mm) Silk dome, Ferrofluid cooled, pivoting, in acoustic back chamber
- Woofer: 6-1/2" (135mm) Carbon fiber cone, pivoting, rubber surround
- Frequency Response: 43Hz - 20kHz, +/-3dB
- Impedance: 8 Ohms nominal; 6 Ohms minimum
- Power Handling: 5 watts minimum; 135 Watts maximum
- Sensitivity: 90dB SPL (2.83V 1 meter)
- Grille Material: Perforated aluminum
- Adjustments: +/-3dB tweeter level

Approximate Weight:

- Shipping: 10 lbs/ pair

Qty: 6 **SONANCE S623TR**
